

MINI VANDAL DOME CAMERA WITH HDMI OUTPUT



Elevate your security with our new security camera with HDMI output, featuring a 2.8mm lens and 2MP resolution for crystal-clear images. It offers flexible power options with DC 12V or PoE, while its intelligent face detection and customizable deterrence messages enhance security. With audio in/out capabilities, you can communicate seamlessly. Upgrade your surveillance and safeguard your store with confidence.



D3F28IP2MP-HDMI



2MP RESOLUTION



2.8MM LENS



IR UP TO 20M



DC12V OR POE



HDMI OUTPUT



AUDIO IN/OUT



CUSTOM DETERRENCE
MESSAGE



DUSTPROOF &
WATER-RESISTANT



MICRO SD CARD SLOT
UP TO 1TB



D3F28IP2MP-HDMI



CAMERA

IMAGE SENSOR	1/2.9" 2MP Progressive Scan CMOS
FILTER	Removable IR Cut Filter
IMAGE SENSOR	1/2.9" 2M Progressive Scan CMOS
LENS	2.8mm IR Lens
RESOLUTION	1920(H)× 1080(V)
ELECTRONIC SHUTTER	NTSC:1/30-1/100,000s PAL:1/25-1/100,000s
MIN ILLUMINATION	0Lux
AVAILABLE IR RANGE	15-20M

VIDEO & AUDIO

VIDEO COMPRESSION	H.264 / H.265
TRANSMISSION STREAM RATE	Dual Stream (Code Rate:36Kb-16M)
FRAME RATE	1-25fps (PAL) ,1-30fps (NTSC)
AUDIO COMPRESSION	G711A, G711U

EXTERNAL INTERFACE

HDMI 1.4	1080P/30FPS
NETWORK INTERFACE	RJ45*1 10M/100M
AUDIO INTERFACE	input/output*1
ALARM INTERFACE	input/output*1

NETWORK

PROTOCOL	IPv4, IPv6, DHCP, HTTP, Onvif, DNS, DDNS, FTP, UPNP, RTSP, SMTP, NTP
NETWORK SUPPORT	ONVIF Profile S, API
MAXIMUM USERS	10
WEB LANGUAGE	English, Simplified Chinese, Traditional Chinese

FUNCTION

IMAGE SETTING	Contrast, Brightness, Sharpness, Saturation , WDR, 3DNR, HLC, BLC
STORAGE	NVR, VMS, TF Card (MAX 1TB)
VIDEO TYPE	Manual, Timing, Motion Detection, Alarm Video
ALARM TRIGGERS	Motion Detection, Alarm
ALARM EVENT	Snapshot, Video, Alarm Output, Email Upload
SYSTEM/EXPLORER SUPPORT	IE, Chrome, Firefox, Safari
GENERAL FUNCTION	Flashing, Mirror, OSD information overlay, Camera angle

GENERAL

POWER SUPPLY	DC12V±10%, POE
CURRENT CONSUMPTION	570mA (MAX)
DIMENSION	Ø114× 82mm
WEIGHT	600g
STORAGE TEMPERATURE	-30° ~ +60°
OPERATING TEMPERATURE	-30° ~ +40°
IP RATING	IP67



2024 Global Surveillance Distribution, G.S.D Group and G.S.D are registered trademarks of Global Surveillance Distribution Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product Without notice and without incurring any obligation.

